



**BEACH  
CONSTRUCTION  
GROUP**



**BEACH PAINTING  
CONTRACTORS**

**CONSTRUCTION PRE-EMPLOYMENT EXAM**

<b>NAME:</b>		<b>DATE:</b>	
<b>TRUE/FALSE</b>			
Studs may be notched up to 75% of their depth.		One square of siding will cover 100 square feet	
<input type="checkbox"/> TRUE		<input type="checkbox"/> TRUE	
<input type="checkbox"/> FALSE		<input type="checkbox"/> FALSE	
Fire blocking is used to slow down the spread of fire.		Backerboard (cement board) is an excellent base for tile.	
<input type="checkbox"/> TRUE		<input type="checkbox"/> TRUE	
<input type="checkbox"/> FALSE		<input type="checkbox"/> FALSE	
The device used to adapt ladders for use as a scaffold is called a ladder jack.		1/8" equals .125 inches.	
<input type="checkbox"/> TRUE		<input type="checkbox"/> TRUE	
<input type="checkbox"/> FALSE		<input type="checkbox"/> FALSE	
<b>MULTIPLE CHOICE</b>			
How deep is a typical kitchen wall cabinet?		The crown of a floor joist must be placed _____	
<input type="checkbox"/> a. 12 inches		<input type="checkbox"/> a. on bottom	
<input type="checkbox"/> b. 18 inches		<input type="checkbox"/> b. on its side	
<input type="checkbox"/> c. 24 inches		<input type="checkbox"/> c. on top	
<input type="checkbox"/> d. 36 inches		<input type="checkbox"/> d. none of the above	
The actual size of a 2x4 is _____		A cut made across the grain of a board is known as a	
<input type="checkbox"/> a. 2" x 4"		<input type="checkbox"/> a. cut back	
<input type="checkbox"/> b. 1-1/2" x 3-1/2"		<input type="checkbox"/> b. back cut	
<input type="checkbox"/> c. 2-1/2" x 4"		<input type="checkbox"/> c. rip cut	
<input type="checkbox"/> d. 1-1/2" x 4"		<input type="checkbox"/> d. cross cut	

<b>MULTIPLE CHOICE (continued)</b>	
Plain bevel siding must overlap at least _____ inch(es)	A 32-inch door should have a rough opening of _____
<input type="checkbox"/> a. 2	<input type="checkbox"/> a. 34"
<input type="checkbox"/> b. 3	<input type="checkbox"/> b. 32"
<input type="checkbox"/> c. 1	<input type="checkbox"/> c. 36"
<input type="checkbox"/> d. 4	<input type="checkbox"/> d. 42"
An 8d common nail is _____ inches long.	What type of door consists of stiles, panels, and rails?
<input type="checkbox"/> a. 1-1/2	<input type="checkbox"/> a. Bi-fold door
<input type="checkbox"/> b. 3	<input type="checkbox"/> b. Raised panel door
<input type="checkbox"/> c. 2-1/2	<input type="checkbox"/> c. Flush panel door
<input type="checkbox"/> d. 4	<input type="checkbox"/> d. None of the above
What board is nailed to the end of a rafter tail?	A full-length stud adjacent to a door or window opening is called a _____ stud.
<input type="checkbox"/> a. gutter	<input type="checkbox"/> a. joist
<input type="checkbox"/> b. fire-blocking	<input type="checkbox"/> b. trimmer
<input type="checkbox"/> c. sheet rock	<input type="checkbox"/> c. king
<input type="checkbox"/> d. fascia	<input type="checkbox"/> d. cripple
The bottom horizontal framing member attached to the floor is called the _____ plate	The top step of a ladder may be used as a step _____
<input type="checkbox"/> a. sole	<input type="checkbox"/> a. if the ladder is secured
<input type="checkbox"/> b. cup	<input type="checkbox"/> b. if it is necessary to reach the work
<input type="checkbox"/> c. header	<input type="checkbox"/> c. never
<input type="checkbox"/> d. footer	<input type="checkbox"/> d. if it is rated for 300 lbs or better
If a room is 15 ft. by 10 ft., how many square feet will the floor have?	The government agency that established national construction safety standards is:
<input type="checkbox"/> a. 25 SF	<input type="checkbox"/> a. ASA
<input type="checkbox"/> b. 1500 SF	<input type="checkbox"/> b. ANSI
<input type="checkbox"/> c. 150 SF	<input type="checkbox"/> c. UL
<input type="checkbox"/> d. 80 SF	<input type="checkbox"/> d. OSHA