



**BEACH PAINTING CONTRACTORS, INC.  
PRE-EMPLOYMENT EXAM**



**NAME OF APPLICANT:** \_\_\_\_\_ **DATE:** \_\_\_\_\_

**TRUE / FALSE**

<p>ONE MIL EQUALS .001 OF AN INCH</p> <p>TRUE FALSE</p>	<p>THE MSDS IS THE START-OF-THE ART SURFACE PREP TOOL</p> <p>TRUE FALSE</p>
<p>OAK IS A COMMON SOFTWOOD</p> <p>TRUE FALSE</p>	<p>“CUTTING IN” IS GENERALLY DONE WITH A ROLLER</p> <p>TRUE FALSE</p>
<p>THE MOST COMMON REASON FOR PAINT FAILURE IS MOISTURE.</p> <p>TRUE FALSE</p>	<p>THE DEVICE USED TO ADAPT LADDERS FOR USE AS A SCAFFOLD IS CALLED A LADDER JACK</p> <p>TRUE FALSE</p>
<p>GREEN IS A PRIMARY COLOR.</p> <p>TRUE FALSE</p>	

**MULTIPLE CHOICE**

<p>NYLON BRUSHES ARE BEST USED TO APPLY:</p> <p>OIL PAINT LATEX PAINT EPOXY PAINT POLYURETHANE PAINT</p>	<p>WHAT IS A NATURAL BRISTLE BRUSH NORMALLY USED FOR?</p> <p>CLEANING OFF WOOD BEFORE PAINTING LATEX PAINTS OIL-BASED PAINTS FOR CLEANING TOOLS AND EQUIPMENT</p>
<p>ACRYLIC PAINT:</p> <p>HAS GOOD COLOR RETENTION ADHERES BETTER THAN EPOXY HAS SUPERIOR ABRASIVE RESISTANCE ALL OF THE ABOVE</p>	<p>WHAT IS A “PAINTER’S HOLIDAY”?</p> <p>A DAY MISSED 1<sup>ST</sup> FRIDAY OF EACH MONTH SOMETHING NOT COMPLETELY PAINTED A JOB WELL DONE</p>
<p>A “LANYARD” IS GENERALLY USED:</p> <p>FOR DEEP SEA FISHING TO APPLY FIBERGLASS LININGS TO ATTACH A “SAFETY HARNESS” TO A ROPE GRAB TO SECURE SCAFFOLD ANCHOR</p>	<p>WHAT IS 220 GRIT SANDPAPER NORMALLY USED FOR?</p> <p>FOR CLEANING EQUIPMENT FOR SANDING FINE FINISHES FOR SANDING DRYWALL SURFACES FOR AUTOMOTIVE FINISHES ONLY</p>

**MULTIPLE CHOICE (CONTINUED)**

<p>THE TECHNICAL TERM FOR A SURFACE TO WHICH PAINT IS APPLIED IS:</p> <p>HOUSE SUBSTRATE WOOD PLASTER</p>	<p>ETCHING A CONCRETE SURFACE DOES WHAT?</p> <p>ADDS WATER PROVIDES "TOOTH" NOTHING CHALKING</p>
<p>THE THICKNESS OF A COAT OF PAINT IS MEASURED IN:</p> <p>MILS LITERS CENTIMETERS GRAMS</p>	<p>FLASH POINT REFERS TO THE TEMPERATURE AT WHICH A MATERIAL BECOMES:</p> <p>VOLATILE FLAMMABLE POISONOUS LIQUID</p>
<p>HOW MANY QUARTS ARE IN ONE U.S. GALLON?</p> <p>8 16 2 4</p>	<p>AN EXTENSION LADDER'S DISTANCE FROM THE BASE OF A BUILDING SHOULD BE WHAT PROPORTION OF ITS TOTAL EXTENSION?</p> <p>1/8 1/3 1/2 1/4</p>
<p>ONE GALLON OF LATEX PAINT WILL COVER APPROXIMATELY HOW MANY SQUARE FEET?</p> <p>100 SQ. FT. 800 SQ. FT. 500 SQ. FT. 250 SQ. FT.</p>	<p>SHELLAC IS THINNED WITH:</p> <p>MINERAL SPIRITS ZYLOL WATER ALCOHOL</p>
<p>THE MOST COMMON SOLVENT USED TODAY FOR THINNING ALKYD PAINT IS:</p> <p>WATER MINERAL SPIRITS MEK LACQUER THINNER</p>	<p>THE GOVERNMENT AGENCY THAT ESTABLISHES NATIONAL CONSTRUCTION SAFETY STANDARDS IS:</p> <p>ASA OSHA PDCA SSPC</p>
<p>A WHITE DEPOSIT ON A MASONRY SURFACE IS KNOWN AS:</p> <p>LEAD BLEED EFFLORESCENCE CHIPPING</p>	<p>IF A ROOM IS 14 FT. BY 10 FT., HOW MANY SQUARE FEET WILL THE CEILING HAVE?</p> <p>24 SQ. FT. 1400 SQ. FT. 140 SQ. FT. 80 SQ. FT.</p>